

GENERAL NOTES

- 1. CONCRETE TO BE MIX. NO.6 (4500 P.S.I.)
- 2. REINFORCING-2 LAYERS OF 4x4-W40xW40 WELDED WIRE FABRIC.
- 3. THREADED PLASTIC INSERTS TO BE PROVIDED FOR HANDLING.
- 4. PIPE OPENINGS TO BE PROVIDED AS REQUIRED. FOR SIZE, LOCATION AND INVERT ELEVATIONS REFER TO CONSTRUCTION PLANS.
- 5. FOR GRATE DETAILS SEE STANDARD MD-378-05. GRATE TO BE AS SHOWN OR FURNISH APPROVED EQUIVALENT.
- 6. "MINIMUM DEPTH" PAYMENT PER "EACH" INLET INCLUDES DEPTHS UP TO 3'-6". VERTICAL DEPTH PAYMENT PER "LINEAR FOOT" FOR DEPTHS IN EXCESS OF 3'-6".
- 7. THIS INLET IS TO BE USED IN MEDIAN DITCHES AND ANY DITCH BEYOND THE SHOULDER AREA. THIS INLET IS NOT TO BE USED IN ROADWAY OR SHOULDER PAVEMENT AREAS OR WHERE BICYCLE OR MOTORCYCLE TRAFFIC IS ANTICIPATED.



SECTION B-B SINGLE OPENING



SPECIFICATION 305

CATEGORY CODE ITEMS

APPROVED

Kik G. M. Call DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT

DOUBLE OPENING



APPROVAL • APPROVAL • FEDERAL REVISIONS HIGHWAY ADMINISTRATION APPROVAL 6-4-84 APPROVAL 8-1-84 REVISED 10-1-01 REVISED 6-23-87 REVISED REVISED REVISED

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

SINGLE OPENING

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

PRECAST STANDARD SINGLE OR DOUBLE OPENING TYPE K INLET OPEN-END GRATE

STANDARD NO.

MD 378.11